


# HPL Wires. A truly safe decision.

**HPL Wires**  
**100% COPPER**  
**FLAME RETARDANT**  
**DOUBLE INSULATION**  
with Ultra Thin Layer



## Domestic Wires

Owing to our consistent efforts for quality and providing the best, we have developed exhaustive range of domestic wires and cables suitable to Indian homes and varied conditions. Manufactured with best quality of Conductor (100% pure electrolytic grade copper) and finest grade of indigenously developed PVC compound, HPL Wires and Cables give maximum safety at no extra cost.



## Construction

Conductor - Annealed Bare Copper

Insulation - Double layer FR grade PVC insulation with inner layer of natural PVC and very thin outer layer of colour PVC.

Standard - IS: 694

Sizes - 0.5 sq. mm to 400 sq. mm

## Applications

HPL Single core wires can be used in duct, conduit, or Aerial wiring for electric power in:

• HOUSES • BUILDINGS • FLATS • APARTMENTS • HOSPITALS • FACTORIES

## Salient Features

- Electrolytic Grade copper having 100% purity and maximum conductivity to ensure maximum safety.
- Bunching of Copper in uniform lay & diameter that makes stripping and crimping of wires easier and minimizes losses.
- Indigenously developed PVC compound formulated from finest ingredients and produced in-house.
- Double insulation, with primary insulation from virgin PVC, coated with ultra thin colour layer.

**HPL** PVC Insulated Single Core Unsheathed Industrial (Multistrand) Cables-Flame Retardant (FR) Conforming To IS:694 With Copper Conductor For Voltage Grade Upto 1100 Volts .

Nominal area of Conductor Sq. mm	Conductor Construction (No./dia.mm)	Standard packing 90m Code (No. of Coils)	Product Code	MRP (Rs.) per FR PVC in 90m Coil	Product Code	MRP (Rs.) per FR PVC in project Packing 180m Coil
0.75	24/2	20	HFR000075090	1013	HFR000075180	2026
1.00	14/3	20	HFR000100090	1310	HFR000100180	2620
1.50	22/3	16	HFR000150090	1903	HFR000150180	3806
2.50	36/3	12	HFR000250090	3108	HFR000250180	6216
4.00	56/3	4	HFR000400090	4697	HFR000400180	9394
6.00	84/3	4	HFR000600090	6905	HFR000600180	1381

Standard Packing - 90mtrs. In carton Project packing - 180mtrs., Poly wrapped

Colour available - Red - RD, Yellow - YL, Blue - BL, Black - BK, Green - GR, White - Wh & Grey - GY, Other colours can be supplied on request, subject to Minimum Order quantity.

supplied on request, subject to Minimum Order quantity.

(Please specify the colour code while ordering & order should be in multiple of standard packing per colour.



Wires & Cables

Ab roshan ho khushiyaan

**HPL PVC Insulated Single Core Unsheathed Industrial (Multistrand) Cables-Flame Retardant Low Smoke and Halogen (FR-LSH) Conforming To IS:694 With Copper Conductor For Voltage Grade Up to 1100 Volts .**

Nominal area of Conductor Sq. mm	Conductor Construction (No./dia.mm)	Standard packing 90m Code (No. of Coils)	Product Code	MRP (Rs.) per FR PVC in 90m Coil	Product Code	MRP (Rs.) per FR PVC in project Packing 180m Coil
1.00	14/.3	20	HHF000100090	1432	HHF000100180	2864
1.50	22/.3	16	HHF000150090	2156	HHF000150180	4312
2.50	36/.3	12	HHF000250090	3396	HHF000250180	6792
4.00	56/.3	4	HHF000400090	5081	HHF000400180	10162
6.00	84/.3	4	HHF000600090	7796	HHF000600180	15592

**HPL Multi Core Flexible Copper Conductor PVC insulated and Sheathed Cables, 1100 Volt Conforming to IS:694**

Nominal area of Conductor Sq. mm	Conductor Construction (No./dia.mm)	Product Code	MRP (Rs.) 2 Core per 100m Coil	Product Code	MRP (Rs.) 3 Core per 100m Coil	Product Code	MRP (Rs.) 4 Core per 100m Coil
0.50	16/.20	HMI2C000050100	2628	HMI3C000050100	3405	HMI4C000050100	4173
0.75	24/.20	HMI2C000075100	3388	HMI3C000075100	4470	HMI4C000075100	5753
1.00	32/.20	HMI2C000100100	4138	HMI3C000100100	5753	HMI4C000100100	7159
1.50	30/.25	HMI2C000150100	5649	HMI3C000150100	7857	HMI4C000150100	9961
2.50	50/.25	HMI2C000250100	9036	HMI3C000250100	12275	HMI4C000250100	16710
4.00	56/.30	HMI2C000400100	13270	HMI3C000400100	19189	HMI4C000400100	25055
6.00	84/.30	HMI2C000600100	20472	HMI3C000600100	27561	HMI4C000600100	36134
10.00	80/.40	HMI2C001000100	33925	HMI3C001000100	48242	HMI4C001000100	63223
16.00	126/.40	HMI2C001600100	52991	HMI3C001600100	74668	HMI4C001600100	99697
25.00	196/.40	HMI2C002500100	81486	HMI3C002500100	116249	HMI4C002500100	153613
35.00	276/.40	HMI2C003500100	111901	HMI3C003500100	161051	HMI4C003500100	212934
50.00	396/.40	HMI2C005000100	159995	HMI3C005000100	230961	HMI4C005000100	305201
70.00	556/.40	HMI2C007000100	225636	HMI3C007000100	330081	HMI4C007000100	429560
95.00	756/.40	HMI2C009500100	291835	HMI3C009500100	427726	HMI4C009500100	563478
120.00	954/.40	HMI2C012000100	369340	HMI3C012000100	538152	HMI4C012000100	738715

Standard Packing - 100mtrs. Per Coil

Note : 70Sq.mm and onwards as per IS:694/1990

**Terms & Conditions**

- All prices are in Indian rupees.
- Prices prevailing at the time of despatch shall be applicable.
- All Prices are Maximum Retail Prices (MRP) inclusive of Excise Duty.
- Prices are exclusive of VAT/CST, Local taxes which as levied, shall be charged extra at actuals.
- Goods are despatched by us on Purchaser's risk.
- All claims of losses, damages or shortages will be filed by the purchaser directly with the carriers.
- This Price List supersedes all our previous Price Lists, and are subject to change without prior notice.
- Company reserves the right to issue amendments, which may arise due to any errors in Price List.
- All disputes are subject to Delhi Jurisdiction.
- For Technical details kindly refer our technical catalogues.

**Notes**

- This price List is subject to change without notice .
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS : 8130:1984 with its related classes and tables.
- Freight : F.O.R. by road transport to any station in India subject to Minimum Order Quantity However, HPL reserves the right charge suitable freight for remote areas.

**General Terms**

- The Price list has been made as per standard length packing if any non-standard packing, the packing charges will be extra.
- Minimum Order quantity acceptable above 35 Sq.mm should be 500 mtrs. ±5%



**HPL Electric & Power Ltd.**

1/21, Asaf Ali Road, New Delhi-110002 Ph.: +91-11-23234411  
Fax : +91-11-23232639 E-mail : hpl@hplindia.com

[www.hplindia.com](http://www.hplindia.com)